

### Oil Bath Air Cleaners - SA Series

Model No.	Rated Airflow C.F.M.	Oil Cap. Pints	A (In.)	B (In.)	C (In.)	D (In.)	E (In.)	F (In.)	G (In.)	H (In.)	K (In.)	L (In.)	M (In.)	Internal Thread	Net Wt. LBS
SA60	100	1.10	6.12	7.12	4.56	2.06	3.38	2.81	2.44	0.50	2.87	3.75	4.25	3/8-16NC2	3.60
SA78	160	1.00	7.80	7.25	5.56	2.56	4.25	3.31	2.25	0.50	2.88	3.75	4.25	3/8-16NC2	5.70
SA90	240	1.80	9.06	8.25	6.56	2.56	4.88	3.46	3.00	0.62	2.88	3.75	4.25	3/8-16NC2	7.30
SA90C	240	1.80	9.06	8.25	6.56	2.56	4.88	3.47	3.00	1.00	2.88	3.75	4.25	3/8-16NC2	7.30
SA90P	240	1.80	9.06	8.25	6.56	2.56	4.88	3.45	4.50	0.62	2.88	3.75	4.25	3/8-16NC2	7.30
SA110	425	3.50	11.00	12.80	8.03	3.50	6.00	5.18	5.25	1.75	3.88	7.50	5.50	1/2-13NC2	15.00
SA110R	425	3.50	11.00	12.80	8.50	3.50	6.00	5.19	5.25	1.75	3.88	5.81	5.50	1/2-13NC2	15.00
SA120	540	5.80	12.12	13.90	10.00	3.50	6.50	7.25	6.63	2.38	3.88	6.25	5.50	1/2-13NC2	20.80

### Metric Measurements

Model No.	Rated Airflow m <sup>3</sup> /h	Oil Cap. Liters	A (mm.)	B (mm.)	C (mm.)	D (mm.)	E (mm.)	F (mm.)	G (mm.)	H (mm.)	K (mm.)	L (mm.)	M (mm.)	Internal Thread	Net Wt. KG
SA60	169	0.52	155.48	180.85	115.82	52.32	85.85	71.37	61.98	12.70	72.90	95.25	107.95	3/8-16NC2	1.63
SA78	271	0.47	198.12	184.15	141.22	65.02	107.95	84.07	57.15	12.70	73.15	95.25	107.95	3/8-16NC2	2.58
SA90	407	0.85	230.12	209.55	166.62	65.02	123.95	87.88	76.20	15.75	73.15	95.25	107.95	3/8-16NC2	3.31
SA90C	407	0.85	230.12	209.55	166.61	65.02	123.95	88.14	76.20	25.40	73.15	95.25	107.95	3/8-16NC2	3.31
SA90P	407	0.85	230.12	209.55	166.62	65.02	123.95	87.63	114.30	15.75	73.15	95.25	107.95	3/8-16NC2	3.31
SA110	722	1.66	279.40	323.85	203.96	88.90	152.40	131.57	133.35	44.45	98.55	190.50	139.70	1/2-13NC2	6.80
SA110R	722	1.66	279.40	323.85	215.90	88.90	152.40	131.83	133.35	44.45	98.55	147.57	1139.70	1/2-13NC2	6.80
SA120	917	2.74	309.63	352.55	254.00	88.90	165.10	184.15	168.40	60.45	98.55	168.75	139.70	1/2-13NC2	9.43

VORTOX AIR TECHNOLOGY, INC.



VORTOX AIR TECHNOLOGY, INC.

