



## DC Breather Caps



Also available:



Type DA  
Slip-On Tube



Type DB  
External Pipe Thread

Vortox Air Technology, Inc. Breather Caps are designed to be used in both negative and positive pressure atmospheres. In negative pressure, the initial media filters out contamination in the air stream that could potentially harm internal components. When used in a positive pressure application, oil and dirt are captured in the filter media contained within the internal reservoir. As air flow stops, the oil will flow back to its source from the reservoir. The outer media serves as a secondary filter prior to the air re-entering the atmosphere oil free.


### Filter Media

Standard Filter Media is a non-toxic, washable cellular foam. Alternate media of either steel or stainless steel mesh is also available.

### Service Instructions

Periodically inspect for accumulation of dirt. Remove Breather Cap, wash in common detergent and rinse. Allow media to dry, then reinstall Breather Cap.

## Breather Caps - DC Series: Internal Pipe Thread



Models available in  
stainless steel.

### MEDIA

1. Foam
2. Woven Steel Wire
3. Stainless Steel Wire

\*Not available with condensing chamber

Model No.	A (In.) NPTF	B (In.)	C (In.)	D (In.)	Net Wt. LBS.	Media
DC50*	½	2.25	1.75	0.50	0.35	1
DC75*	¾	2.25	1.75	0.50	0.50	1
DC100	1	3.25	2.75	0.75	0.90	1
DC125	1¼	3.25	2.75	0.75	1.00	1
DC125B	1¼	5.06	3.43	0.82	2.40	2
DC125D	1¼	3.25	2.75	0.75	2.20	2
DC125E	1¼	3.26	2.75	0.75	2.20	2
DC150	1½	3.25	2.75	0.75	1.25	1
DC150B	1½	3.26	2.75	0.75	1.25	2
DC200	2	5.06	3.44	1.00	2.50	1
DC300	3	6.56	4.50	1.38	5.50	1
DD75A	¾	2.25	1.75	1.19	0.06	1



AUSTRALIAN OWNED  
& OPERATED

[www.vortox.com](http://www.vortox.com)

F-3007  
250617